

I/O Matrix

[To Main Page](#)

Mode: Mono (2 ch)
Channels: 1
Line Vrms: 120



Ref			A	B	C				D	E	F	G	H			I	J	K	L		M
			Audio (per channel)							Supply (total)					Thermal Output						
Stimulus	Stimulus	Crest Factor	Load R	dBu In	Vrms Out	Loading Eff. (dB)	Rated Watts	Meas. Watts	Meas. dBW	Amps	Watts	Power Factor	BTU/hr	kCal/hr							
1	Burst	CEA2006 1 kHz	17	8	1.8	91	0	780	1035	30											
				4	0.6	82	-1	1160	1681	32											
				2																	
		1% THD																			
2	Burst	CEA2006 50 Hz	17	8	0.7	83	0		861	29											
				4	0.6	71	-1	1260	31												
				2																	
		3% THD																			
3	Tone	1 kHz 15 sec	3	8	0.0	78	0		761	29	13.8	1325	0.80	1925	485						
				4	-2.0	61	-2	930	30	20.0	1992	0.83	3623	913							
				2																	
4	Tone	50 Hz 15 sec	3	8	0.0	77	0		741	29	13.8	1325	0.80	1991	502						
				4	-2.0	61	-2	930	30	20.3	2022	0.83	3725	939							
				2																	
5	Noise	Pink 60 sec	9	8	-6	40	0		200	23	8	730	0.76	1807	455						
				4	-6	40	0	400	26	15	1440	0.80	3548	894							
				2																	
		1/4 Power																			
6	Noise	Pink 60 sec	12	8	-9	30	0		113	21	6	533	0.74	1434	361						
				4	-9	30	0	225	24	11	1030	0.78	2745	692							
				2																	
		1/8 Power																			
7	Inrush Current																				
8	Idle ("On" but no signal)										0.64	52	0.68	178	45						
9	Standby																				